



DOMINATOR™ SHED MASTER®

DESIGNED FOR ALL WEATHER

TOUGH AND TECHNICAL – A GREAT ALL ROUNDER

Dominator™ ShedMaster® features a tough, IP24 rated weather resistant housing and is perfect for exposed applications like perimeter doors and self storage units. With a keyed lockout for added security and slim fit design, it is perfect for harsh environments.

And just because it's rugged doesn't mean this roll-up door opener doesn't have brains. Standard features also include Intelligent Safety System, Door Profiling and Automatic Technology's own TrioCode™ 128 transmitter system. This opener will tell you when it's due for a service and prevents unauthorised entry with a built-in lockout system. If you need a solution to last in all weather conditions then this is the opener for your door.

WHAT'S IN THE BOX:



Weather Resistant Opener



Two TrioCode™ 128 transmitters



Keyed Lockout



Wired Safety Beams

AT A GLANCE:




WEATHER-RESISTANT HOUSING

Designed for installation on uncovered or exposed doors, this opener has a weather resistant rating of IP24.

SECURE & RELIABLE TRANSMITTERS

The TrioCode™ 128 transmitter system ensures secure and reliable home access. It transmits on three frequencies to defeat radio interference, and uses a 128-bit encryption protocol (with trillions upon trillions of random codes*) for the ultimate in security.



340,282,366,920,938,463,463,374,607,431,768,211,456 codes

KEYED & ELECTRONIC LOCKOUT

As the Shed Master® can be installed in exposed locations, a keyed lockout is included to stop unwanted persons reaching over the fence and disengaging the door to manual mode. Also, the control panel can be similarly locked out to prevent unauthorised usage.

INTELLIGENCE

This opener is top of its range with built-in intelligent features such as Intelligent Safety System and Door Profiling – meaning the door adjusts itself when opening and closing or if blocked.

DOMINATOR™ SHED MASTER®



TECHNICAL SPECIFICATIONS

Power	Input Voltage	120V a.c. / 60 Hz
	Transformer Rating	72VA
	Standby Power	2.8W
	Motor Type	24V d.c. Permanent Magnet
	Motor Power	100W
Door Sizes	Peak Driving Force	550N
	Rated Door Area	165ft ²
Transmitter System	Typical Travel Speed (door dependent)	4"/sec
	Receiver/Transmitter Frequency	Multi-frequency UHF FM (433.47, 433.92 & 434.37MHz)
	Coding System	Code hopping (Non-linear encryption algorithm)
	Code Combinations	3.4x10 ⁹⁸ code combinations
	Transmitter Type	TrioCode™ 128
Additional Features	Transmitter Capacity (x 4-button registers)	8
	Weather Resistance Rating	IP24
	Lockout system	Keyed lockout for manual release Electronic lockout for control panel buttons
Warranty	Safety Beam Included	1 set x 3-wire Safety Beam
		2 year/5,000 cycles

SAFETY & SECURITY FEATURES



Intelligent Safety System



Door Profiling



**128
TrioCode™ 128**

POWER & MOUNTING SYSTEMS



DC Motor - 550N



Slim Fit

OPERATING MODES & FEATURES



Weather Resistant



Service Indicator



Lockout System

See our website for our icon glossary explanations.

Member of:  

Approved by:  

Automatic Technology America
Vineyard Centre II, 1452 Hughes Road, Grapevine, Texas 76051, United States of America

**SMART
SIMPLE
SECURE**

©2017 Automatic Technology America. All rights reserved. The Automatic Technology logos, "smart simple secure" wordage, feature icons and Dominator™ are trademarks and registered trademarks of Automatic Technology Australia Pty Ltd. No part of this brochure may be reproduced without prior permission. In an ongoing commitment to product quality we reserve the right to change specification without notice. E&OE. Vineyard Centre II, 1452 Hughes Road, Grapevine, Texas 76051, United States of America.

For more information on this door opener and other Automatic Technology products please visit us online at www.ata-america.com

automatic
TECHNOLOGY